



## PALLET DOLLY TOPL140

**UNLADEN WEIGHT,**  
2750 KGS. APPROX.

**CARRYING CAPACITY,**  
14,000 kgs. At a speed of 16 kph.

**ULD & CONTAINER CAPABILITY.**  
1 no. 238.5" x 96" (20ft Aircraft Pallet.)  
2 no. 125" x 96" pallet or container.  
2 no. 125" x 88" pallet or container.

**LOAD BED.**  
Three rows of heavy duty 75mm. Diam. Rollers separated by two grip faced steel walkways. Continuous guides on each side and across the front allow for loads to be rolled on and off the rear of the bed.  
Manual lift- up stops are located to suit the various Containers & Pallets catered for.

**RUNNING GEAR.**  
Four twin wheeled rocking axle swivel casters are fitted to the front of the unit. Wheels are 15" diameter x 4.5" wide. Rear wheels are on 4 fixed caster mountings with rocking axles.  
Super Elastic 3-stage rubber tyres are fitted to all wheels. The 16 wheels are attached to 5 stud wheel hubs.

**STEERING.**  
Controlled by the 4 front swivel casters.  
Minimum swept radius 6.5M

### BRAKES.

Parking brakes operate on the periphery of the rear wheels and are of the pram brake type, operating on all eight rear wheels. They are actuated by the tow bar being latched in the vertical position.

### STANDARD COUPLINGS.

**The Towbar** - has a towing-eye with 75mm diameter hole, the ring-section of the eye is 30mm diameter. A grip-handle is provided on top of the towbar. Towbar is spring damped to remain at towing height level.

### STANDARD FINISH .

Double paint coat finish as per customer requirements  
High-Visibility markings on surround-frame corners and both sides of towbar.

### OPTIONS - EXTRAS.

- Additional Stops for other ULD types
- Alternative coupling types
- Painted Finish to Client's requirements
- Special corporate or identification markings.
- Additional visibility markings.

